

PB3600

specifications



utilities	<p><i>AC Input Power:</i> 100 to 240 Vac 50/60 Hz, Single Phase @ 15A service <i>AC Fuse:</i> 10A @ 115 VAC; 5A @ 240 VAC <i>Vacuum Supply:</i> Input: ≥ 25" of Mercury <i>Requirements:</i> Consumption: 3 SCFM <i>Air Pressure:</i> None Required</p>	
mechanical specifications	<p><i>Physical Dimensions:</i> Height: 54" (137 cm) Width: 63" (160 cm) Depth: 43" (109 cm) Weight: 759 lbs. (344 kg) Tie Down: Earthquake Tie Down Provided Portability: 12 Rolling Casters & 8 Heavy-Duty Rubber Feet Provided</p> <p><i>Wafer / Measurement Stage:</i> Diameter: 11" X 9.5" Semi-Round Flatness: 0.0002" TIR Planarity Test Area: 12" x 8" Raised Isolation Pin: 3 mil Std. (1-5 mil optional) Customer Changeable Flush Isolation Pin: 3 mil Std. (1-5 mil optional) Customer Changeable No. of Isolation Pins / Chuck: 3 Different Size or Type Isolation Pins at the Same Time Gram Force Pin: 3 mil Std. (1-5 mil optional) Customer Changeable Max Total Probe Tip Force: 220 lb. (100 kg) Travel: X = 12" (30.5 cm), Y = 8" (20.3 cm), Z = 0.75" (1.9 cm)</p> <p><i>Test Channel Multiplexer:</i> Type: Solid State, Kelvin Connections, Cableless, RID MUX Size/Modularity: Up to 3072 Channels in 64 Channel Increments Each channel can be software selected to be either a test channel or relay drive channel.</p> <p><i>Hinged Probe Card Adapter:</i> Accommodates: Various ITC Motherboards & Flipping of Probe Card for Repair Operation: Motorized Elevator</p> <p><i>Video System:</i> Alignment Resolution: 0.1 micron Type: B/W No. of Probes / Capture: 1 - Single Pin, 4-12 - Multi-Pin Capture (Pitch Dependent) Min. Probe Size: 0.2 mil Max. Probe Size: 10 mils Upper Video: Live Upper Video Standard</p>	
pc computer	<p><i>Standard Hardware:</i> Processor: Pentium P4, ≥ 3.0 GHz Industrial Computer Operating System: Windows 2000 or XP Pro w/ODBC Database for Programs & Data Hard Drive: ≥ 80 Gb Memory: ≥ 512 MB PC 100 Peripherals: 3.5" Floppy, CD-RW ROM Monitor: High Resolution 19" Color LCD, CE Approved I/O: Ethernet Card, 1 Serial Port, 1 Parallel Port, & USB</p>	
measurement system	<p><i>Number of Channels:</i> (4-Wire Kelvin Measurement) Standard: 1536 Optional: Up to 3,072 Maximum Signal Pins: 3,072 Maximum Total Pins: 10,000</p> <p><i>Compliance Voltage:</i> DC Test Software Adjustable from 3 to 10 Volts DC</p> <p><i>Components:</i> Resistors: Serial & Parallel Capacitors: Parallel</p>	
environmental requirements	<p><i>Ambient Temperature:</i> Operating: 68°F +10°F/-5°F (20°C +6°C/-3°C) Highest Accuracy & Repeatability: 68°F \pm 2°F (20°C \pm 1°C) Storage: 20°F - 102°F (-6°C - 39°C)</p> <p><i>Cleanliness:</i> Recommended: Class 10,000 (or better) Clean Room</p> <p><i>Humidity:</i> (Non-condensing) Operating: 0% - 70% RH Storage: 0% - 80% RH</p>	
motherboards	<p><i>Weight:</i> Motherboard: Approx. 25 lb. (11.4 kg) Retainer: Approx. 17 lb. (7.7 kg) Max. Probe Card Dia.: 19" (45.7 cm) Edge Cards: 4" to 8" (10 to 20 cm) Tools Req'd to Change Card: None Coupling: Repeatably Kinematic Coupling Calibration: Adjustable Planarity to 0.1 mil (2.54 microns)</p>	

Note: Specifications are subject to change without notice.

F.S. = Full Scale of the Given Range

RDG = % of Reading

spec sheet

PB3600

specifications



general	<i>Compliance Standards:</i>		Semi S2-93 & S2-93A	Standard			
	<i>Safety Guidelines:</i>		Semi S8-95 Ergo Guidelines:	Standard			
accuracy specification	electrical measurements	Resistance	0 - 1Ω	7 mA	10V	0.00004Ω	1% F.S. + 0.001Ω
			0 - 10Ω	7 mA	10V	0.0004Ω	1% F.S. + 0.010Ω
			0 - 100Ω	7 mA	10V	0.004Ω	0.5% F.S. + 0.100Ω
			0 - 1kΩ	7 mA	10V	0.04Ω	0.5% F.S. + 1.000Ω
			0 - 10kΩ	0.9 mA	10V	0.347Ω	0.5% F.S. + 10.00Ω
			0 - 100kΩ	10V	1mA	3.125Ω	0.5% F.S. + 100.0Ω
			0 - 1MΩ	10V	10μA	31.25Ω	0.5% F.S. + 1kΩ
			0 - 10MΩ	10V	10μA	312.5kΩ	1% F.S. + 10kΩ
			0 - 100MΩ	10V	10μA	3125kΩ	1% F.S. + 100kΩ
			Leakage	0 - 1μA	10V	10μA	30pA
0 - 10μA	10V	10μA		300 pA	0.1% RDG + 0.010μA		
0 - 100μA	10V	10μA		3,000 pA	0.1% RDG + 0.10μA		
0 - 1000μA	10V	10μA		30,000 pA	0.1% RDG + 1.0μA		
Capacitance	10nF	100μA	10V	10pF	1% F.S. + 10pF		
	100nF	100μA	10V	100pF	1% F.S. + 100pF		
	1μF	1 mA	10V	1nF	1% F.S. + 1nF		
	10μF	1 mA	10V	10nF	1% F.S. + 10nF		
	100μF	10 mA	10V	100nF	1% F.S. + 100nF		
	1,000μF	10 mA	10V	1μF	1% F.S. + 1μF		
	10,000μF	10 mA	10V	10μF	1% F.S. + 10μF		
> 10,000μF	Contact Factory for Specifications						
accuracy specification	physical measurements	Planarity	0.75" (Z)	100 lbs.	0.1 micron	2.0 micron (0.08 mils)	1.0 micron (0.04 mil)
		Alignment	12" x 8" (X x Y)	100 lbs.	0.1 micron	2.0 micron (0.08 mils)	1.2 micron (0.05 mil)
		Gram Force	0 - 30 gram	30 gram	0.1 gram	1% F.S. + 0.1 gram	0.15 grams
			0 - 60 gram	60 gram	0.2 gram	1% F.S. + 0.2 gram	0.30 grams

Note: Specifications are subject to change without notice.

F.S. = Full Scale of the Given Range

RDG = % of Reading

INTEGRATED TECHNOLOGY CORPORATION

1228 North Stadem Drive • Tempe, Arizona 85281 USA • Phone 480-968-3459 • Fax 480-968-3099
Sales@IntTechCorp.com

spec sheet